
Ferrules For 2SN R2AT Braided Hose Fittings



03310

SOCKET FOR 2SN / R2AT HOSE

PART NO.		HOSE SIZE			DIMENSIONS				
		DN	DASH		L	D	d		
03310-03Z		5	03		23	21	14.1		
03310-04Z		6	04		30.5	23	15.7		
03310-05Z		8	05		30	24	17.3		
03310-06Z		10	06		32	26	19.6		
03310-08Z		12	08		34	29	22.8		
03310-10AZ		16	10		35	34.5	26.6		
03310-12Z		20	12		42	37	30.3		
03310-16Z		25	16		51	46.7	38.8		
03310-20AZ		32	20		55	59	49.6		
03310-24AZ		40	24		66	67	56		
03310-32AZ		50	32		72	80	68.8		

1. Part no. marked with "*" is recommended.

2. Matched with braid fitting and ISO 1436 2SN & R2ATS, GB/T 3683 2SN & R2ATS, EN 853 2SN, SAE J517 100R2AT braid hose, and no-skive needed.

3. Material options for socket.

Socket material	Part. No. suffix	Part No. example
Carbon steel (Default)	Z	03310-08Z
304 stainless steel	SR	03310-08SR
316L stainless steel	SV	03310-08SV
316Ti stainless steel	SY	03310-08SY

4. Plating options and performance for carbon steel socket

Plating method	Part. No. suffix	Part No. example	White rust (Hours)	Red rust (Hours)
Cr3+ plating (Default)	Z	03310-08Z	96	360
Durakote plating	ZD	03310-08ZD	360	720
Zinc-nickel plating	ZN	03310-08ZN	1000	-